



Description: Hydraulic powered casing tong, 2 speed, with 3 jaw biting system, built in spring hanger and leveling system, door safety interlock and adjustable relief valve for torque control

Specifications:

- Standard part number 01E13E
- Standard torque 25000 ft-lbs @ 3200 PSI (19550 ft-lbs @ 2500 PSI)
- Standard speed 75 RPM @ 65 GPM
- Upgrade part number 01E13F-30
- Upgrade torque 36000 ft-lbs @ 2450 PSI
- Upgrade speed 36 RPM @ 65 GPM
- Torque arm 32" (tong), 24-3/4" (backup)
- Dimensions Width: 31-3/4", Depth: 53-1/4", Weight: 1175 lbs (without backup)
Width: 38-1/4", Depth: 53-1/4", Weight: 2275 lbs (with backup)
- Tong jaw set part numbers

3-1/2"	4-1/2"	5-1/2"	6-5/8"	7"	7-5/8"
707 13462	707 13457	707 13450	707 13445	707 13440	707 13435
8-5/8"	9-5/8"	10-3/4"	11-3/4"	12-3/4"	13-3/8"
707 13430	707 13425	707 13420	707 13415	707 13410	707 13405

Options:

- Hydraulic lift cylinder kit - 36" 706K00037
- Line pressure torque gauge kit 706 01007-13
- Tension load cell assembly 706 01000-13
- Hydraulic backup 02F14E
- Hydraulic backup installation 706F00032-09
- Compression load cell assembly 706F06150-14
- Backup jaw set part numbers

3-1/2"	4-1/2"	5-1/2"	6-5/8"	7"	7-5/8"
707 14462	707 14457	707 14450	707 14445	707 14440	707 14435
8-5/8"	9-5/8"	10-3/4"	11-3/4"	12-3/4"	13-3/8"
707 14430	707 14425	707 14420	707 14415	707 14410	707 14405

13-5/8" Casing Tong