



Description: Hydraulic powered casing tong, 2 speed, with 3 jaw biting system, built in spring hanger, leveling system, door safety interlock and adjustable relief valve for torque control

Specifications:

- Standard part number 01C17F
- Standard torque 30000 ft-lbs @ 3250 PSI (23070 ft-lbs @ 2500 PSI)
- Standard speed 63 RPM @ 65 GPM
- Upgrade part number 01C17H-30
- Upgrade torque 41000 ft-lbs @ 2350 PSI
- Upgrade speed 31 RPM @ 65 GPM
- Torque arm 36" (tong)
- Dimensions Width: 37-3/4", Depth: 59", Weight: 1800 lbs (without backup)
- Tong Jaw Set Part Numbers

6-5/8"	7"	7-5/8"	8-5/8"	9-5/8"	10-3/4"
707 17455	707 17450	707 17445	707 17440	707 17435	707 17430
11-3/4"	12-3/4"	13-3/8"	16"	16-1/2"	17"
707 17425	707 17420	707 17415	707 17410	707 17408	707 17405

Options:

- Hydraulic lift cylinder kit - 36" 706K00037
- Line Pressure torque gauge kit 706 01007-17
- Tension load cell assembly 706 01000-17
- Hydraulic backup 02E18F
- Hydraulic backup installation 706F00032-18
- Compression load cell assembly 706F06150-18
- Backup Jaw Set Part Numbers

6-5/8"	7"	7-5/8"	8-5/8"	9-5/8"	10-3/4"
707 18455	707 18450	707 18445	707 18440	707 18435	707 18430
11-3/4"	12-3/4"	13-3/8"	16"	16-1/2"	17"
707 18425	707 18420	707 18415	707 18410	707 18408	707 18405

17" Casing Tong