



**Description:** Hydraulic powered casing tong, 2 speed, with 3 jaw biting system, built in spring hanger, leveling system, door safety interlock and adjustable relief valve for torque control

**Specifications:**

- Standard part number 01C20G
- Standard torque 35000 ft-lbs @ 3500 PSI (25200 ft-lbs @ 2500 PSI)
- Standard speed 57 RPM @ 65 GPM
- Upgrade part number 01C20J-30
- Upgrade torque 50000 ft-lbs @ 2450 PSI
- Upgrade speed 28 RPM @ 65 GPM
- Torque arm 42" (tong)
- Dimensions Width: 43-3/4", Depth: 70-1/4", Weight: 2250 lbs (without backup)
- Tong jaw set part numbers

<b>7"</b>	<b>7-5/8"</b>	<b>8-5/8"</b>	<b>9-5/8"</b>	<b>10-3/4"</b>	<b>11-3/4"</b>	<b>12-3/4"</b>
707 20460	707 20450	707 20445	707 20440	707 20435	707 20430	707 20425
<b>13-3/8"</b>	<b>16"</b>	<b>16-1/2"</b>	<b>17"</b>	<b>18-5/8"</b>	<b>20"</b>	
707 20420	707 20415	707 20414	707 20412	707 20410	707 20405	

**Options:**

- Hydraulic lift cylinder kit – 36" 706K00037
- Line pressure torque gauge kit 706 01007-20
- Tension load cell assembly 706 01000-20
- Hydraulic backup 02E21G
- Hydraulic backup installation 706F00032-21
- Compression load cell assembly 706F06150-21
- Backup jaw set part numbers

<b>7"</b>	<b>7-5/8"</b>	<b>8-5/8"</b>	<b>9-5/8"</b>	<b>10-3/4"</b>	<b>11-3/4"</b>	<b>12-3/4"</b>
707 21460	707 21450	707 21445	707 21440	707 21435	707 21430	707 21425
<b>13-3/8"</b>	<b>16"</b>	<b>16-1/2"</b>	<b>17"</b>	<b>18-5/8"</b>	<b>20"</b>	
707 21420	707 21415	707 21414	707 21412	707 21410	707 21405	

**20" Casing Tong**