



Description: Hydraulic powered casing tong, 2 speed, with 3 jaw biting system, built in spring hanger, leveling system, door safety interlock and adjustable relief valve for torque control

Specifications:

- Standard part number 01B24H
- Standard torque 40000 ft-lbs @ 3400 PSI (29300 ft-lbs @ 2500 PSI)
- Standard speed 49 RPM @ 65 GPM
- Upgrade part number 01B24J-30
- Upgrade torque 56000 ft-lbs @ 2375 PSI
- Upgrade speed 24 RPM @ 65 GPM
- Torque arm 48"
- Dimensions Width: 49-3/4", Depth: 78", Weight: 3550 lbs
- Tong jaw set part numbers

8-5/8"	9-5/8"	10-3/4"	11-3/4"	12-3/4"	13-3/8"	16"
707 24460	707 24455	707 24450	707 24445	707 24440	707 24435	707 24430
16-1/2"	17"	18-5/8"	20"	22"	24-1/2"	
707 24425	707 24423	707 24420	707 24415	707 24410	707 24405	

Options:

- Hydraulic lift cylinder kit – 36" 706K00037
- Hydraulic lift cylinder kit – 66" 706K00036
- Line pressure torque gauge kit 706 01007-24
- Tension load cell assembly 706 01000-24

24-1/2" Casing Tong