



Size	3.5
Description	<p>Unitized 3.5 Power Swivel System, with:</p> <ul style="list-style-type: none"> - Swivel Head <ul style="list-style-type: none"> o Max Torque: 8100 ft-lbs o Max Speed: 150 rpm o Nominal Load Rating: 120 tons o 100 RPM Load Rating: 65 tons o Standard saver sub connection: 3"-8 Line Pipe Thread o Goose Neck Access Hole Diameter: 2-1/2" NPT o Max Circulating Pressure: 5000 PSI o Bore thru Stem: 2-1/4" o Elevator Bail: 3-1/2" and 4-1/2" o Gear Oil Capacity: 4-1/2 gallons o High Pressure Hose Size: 1-1/4" o Drain Hose Size: 1" - Engine: CAT C7 or Cummins QSB 6.7 220 HP with electric start <ul style="list-style-type: none"> o Engine control system mounted on a shock isolated panel consisting of tachometer, hour meter, push button, start switch, volt meter, oil pressure gauge, water temp gauge o Safety shutdown system for low oil pressure, high water temperature - Fuel Tank: 100 gallons - Hydraulic Reservoir: 75 gallons - 12v battery and battery box, and utility/tool box - Pneumatic controls with torsion control valve - Hydraulically driven hose reels with 100 feet of hydraulic hose - Remote control panel with 50 feet of hose - Skid mounted or Tandem Axle Gooseneck Trailer
Weight	14000 lbs

3.5 Power Swivel