



Description: Hydraulic powered casing tong, 2 speed, with 2 jaw biting system, built in spring hanger, leveling system, door safety interlock and adjustable relief valve for torque control

Specifications:

- Part number 01F05C
- Maximum torque 15000 ft-lbs @ 2500 PSI
- Maximum speed 102 RPM @ 65 GPM
- Torque arm 26" (tong), 24" (backup)
- Dimensions Width: 24-1/2", Depth: 45", Weight: 850 lbs (without backup)
 Width: 26-1/2", Depth: 45", Weight: 1650 lbs (with backup)
- Tong 4-1/8" jaw set (2-1/16" - 4-1/8") 707 05410 (less dies)
- Tong 5-1/2" jaw set (4-1/4" - 5-1/2") 707 05405 (less dies)
- Wraparound dies 2 each required for each size jaw set

2-1/16"	2-3/8"	2-7/8"	3"	3-1/16"	3-1/8"
707 05260-01	707 05260-02	707 05260-03	707 05260-07	707 05260-18	707 05260-11
3-1/4"	3-3/8"	3-1/2"	3-5/8"	3.67"	3-3/4"
707 05260-13	707 05260-14	707 05260-04	707 05260-24	707 05260-20	707 05260-21
3-7/8"	4.03"	4-1/8"	4-1/4"	4-1/2"	4-5/8"
707 05260-27	707 05260-17	707 05260-31	707 05255-42	707 05255-45	707 05255-46
4-3/4"	5"	5-1/4"	5-1/2"		
707 05255-47	707 05255-50	707 05255-52	707 05255-55		

Options:

- Hydraulic lift cylinder kit - 36" 706K00037
- Line pressure torque gauge kit 706 01007-05
- Tension load cell assembly 706 01000-05
- Hydraulic backup 02F06C
- Hydraulic backup installation 706F00030-05
- Compression load cell assembly 706F06150-06
- Backup 4-1/8" jaw set (2-1/16" - 4-1/8") 707 06430 (less dies)
- Backup 5-1/2" jaw set (4-1/4" - 5-1/2") 707 06420 (less dies)
- Wraparound dies 3 each required for each size jaw set

5-1/2" Casing Tong