



Description: Hydraulic powered casing tong, narrow body, 2 speed, with 2 jaw biting system, built in spring hanger, leveling system, door safety interlock and adjustable relief valve for torque control

Specifications:

- Part number 01C07C
- Maximum torque 17000 ft-lbs @ 3000 PSI (14100 ft-lbs @ 2500 PSI)
- Maximum speed 97 RPM @ 65 GPM
- Torque arm 24" (tong), 24" (backup)
- Dimensions Width: 22", Depth: 46-3/4", Weight: 1100 lbs (w/o backup)
Width: 23", Depth: 46-3/4", Weight: 1775 lbs (with backup)
- Tong 4-1/8" jaw set (2-1/16"- 4-1/8") 707 07427 (less wraparound dies)
- Tong 5-1/2" jaw set (4-1/4" - 5-1/2") 707 07417 (less wraparound dies)
- Wraparound dies 2 each required for each size jaw set

2-1/16"	2-3/8"	2-7/8"	3"	3-1/16"	3-1/8"
707 05260-01	707 05260-02	707 05260-03	707 05260-07	707 05260-18	707 05260-11
3-1/4"	3-3/8"	3-1/2"	3-5/8"	3.67"	3-3/4"
707 05260-13	707 05260-14	707 05260-04	707 05260-24	707 05260-20	707 05260-21
3-7/8"	4.03"	4-1/8"	4-1/4"	4-1/2"	4-5/8"
707 05260-27	707 05260-17	707 05260-31	707 05255-42	707 05255-45	707 05255-46
4-3/4"	5"	5-1/4"	5-1/2"		
707 05255-47	707 05255-50	707 05255-52	707 05255-55		

- Tong 6-5/8" jaw set 707 07415 (with standard flat dies)
- Tong 7" jaw set 707 07410 (with standard flat dies)
- Tong 7-5/8" jaw set 707 07405 (with standard flat dies)

Options:

- Hydraulic lift cylinder kit - 36" 706K00037
- Line pressure torque gauge kit 706 01007-07
- Tension load cell assembly 706 01000-07
- Hydraulic backup 02B07C
- Hydraulic backup installation 706F00030-07
- Compression load cell assembly 706F06150-06
- Backup 4-1/8" jaw set (2-1/16"- 4-1/8") 707 07527 (less wraparound dies)
- Backup 5-1/2" jaw set (4-1/4" - 5-1/2") 707 07517 (less wraparound dies)
- Backup 6-5/8" jaw set 707 07515 (with standard flat dies)
- Backup 7" jaw set 707 07510 (with standard flat dies)
- Backup 7-5/8" jaw set 707 07505 (with standard flat dies)
- Wraparound dies 3 each required for each size jaw set

7-5/8" Casing Tong