



**Description:** Hydraulic powered casing tong, 2 speed, with 3 jaw biting system, built in spring hanger and leveling system, door safety interlock and adjustable relief valve for torque control

**Specifications:**

- Standard part number 01E09D
- Standard torque 22000 ft-lbs @ 3050 PSI (18100 ft-lbs @ 2500 PSI)
- Standard speed 84 RPM @ 65 GPM
- Upgrade part number 01E09E-30
- Upgrade torque 27000 ft-lbs @ 2000 PSI
- Upgrade speed 41 RPM @ 65 GPM
- Torque arm 30" (tong), 24" (backup)
- Dimensions Width: 28-1/2", Depth: 49-1/4", Weight: 1100 lbs (without backup)  
 Width: 32-3/8", Depth: 49-1/4", Weight: 2100 lbs (with backup)
- Tong jaw set part numbers

3-1/2"	4-1/2"	5-1/2"	6-5/8"	7"	7-5/8"	8-5/8"	9-5/8"
707 09436	707 09431	707 09425	707 09420	707 09417	707 09415	707 09410	707 09405

**Options:**

- Hydraulic lift cylinder kit - 36" 706K00037
- Line pressure torque gauge kit 706 01007-09
- Tension load cell assembly 706 01000-09
- Hydraulic backup 02F10E
- Hydraulic backup installation 706F00032-09
- Compression load cell assembly 706F06150-10
- Backup jaw set part numbers

3-1/2"	4-1/2"	5-1/2"	6-5/8"	7"	7-5/8"	8-5/8"	9-5/8"
707 10436	707 10431	707 10425	707 10420	707 10417	707 10415	707 10410	707 10405

**9-5/8" Casing Tong**