



Description: The SPINMASTER drill pipe spinner is a roller chain design and is available in hydraulic or air operation. The hydraulic power requirements are 2000 PSI at 20 GPM. Air requirements are 240 CFM at 100 PSI. The compact design of the unit is easy to handle on rig floors. Changing the tool for different sizes is simple as only two pins have to be removed and then the drive assembly can be moved to the appropriate hole location.

Specifications:

Model	550A	550H	950A	950H
Actuation	Air	Hydraulic	Air	Hydraulic
Size Range	2.88" to 5.5" OD (73 to 139 mm)		2.88" to 9.5" OD (73 to 241 mm)	
Rated Torque (Maximum OD)	1250 ft-lbs (1695 N-m)	1050 ft-lbs (1424 N-m)	2250 ft-lbs (3050 N-m)	1950 ft-lbs (2644 N-m)
Rated Torque (Minimum OD)	600 ft-lbs (813 N-m)	600 ft-lbs (813 N-m)	600 ft-lbs (813 N-m)	600 ft-lbs (813 N-m)
Rated Speed (Maximum OD)	70 RPM	70 RPM	39 RPM	39 RPM
Rated Speed (Minimum OD)	130 RPM	130 RPM	130 RPM	130 RPM
Estimated Weight	950 lbs (431 Kg)	620 lbs (281 Kg)	1025 lbs (465 Kg)	660 lbs (299 Kg)

Drill Pipe Spinner