



Description: The HURRICANE bug blowers are rugged fans designed for maximum air flow, low decibel noise levels, durability and safety. They cool and protect rig crews from irritating flying insects and potentially hazardous downhole gases on the rig floor, both onshore and offshore.

- Each fan utilizes a non-sparking, cast aluminum, two blade impeller complete with OSHA compliant guards.
- The electrical system is UL certified for use in explosion proof or XP areas (Class 1 Div. 1 Groups C&D).
- Standard motor is dual rated for 460 VAC / 3 phase / 60 Hz and 380 VAC / 3 phase / 50 Hz.
- Other motors are available for your custom application.
- A lifting lug is included at the top of the housing to facilitate handling. Forklift pockets can be added to the heavy duty skid base for another option of easy handling.

Specifications:

Model	24	36	48	54
Part Number	HURRICANE24	HURRICANE36	HURRICANE48	HURRICANE54
Motor HP	2	3	5	5
Motor RPM	1800	1200	1200	1200
CFM 60 HZ*	8800	18770	37200	40000
50 HZ*	7000	15400	30000	33000
Noise Level @ 5'	78 dBA	79 dBA	87 dBA	89 dBA
Width	35" 889 mm	42" 1067 mm	54" 1372 mm	60" 1524 mm
Depth	24" 610 mm	32" 813 mm	35" 889 mm	35" 889 mm
Height	41" 1041 mm	70" 1778 mm	78" 1981 mm	84-1/2" 2146 mm
Estimated Weight	300 lbs (136 kg)	420 lbs (190 kg)	500 lbs (227 kg)	585 lbs (265 kg)

*Calculated performance

HURRICANE Bug Blower