



**Description:** The 45000, 55000 and 56000 powered tubing tongs are an open face design. Tongs come complete with spring hanger, torque/pressure gauge and relief valve (less jaws/bushings and backup). The hydraulic requirements are 2500 PSI at 30 GPM, and the tong has a 29" torque arm.

**Specifications:**

Part Number	45000-100	55000-100	56000-100
Rated Torque in Low Gear	6670 ft-lbs (9043 N-m)	8740 ft-lbs (11850 N-m)	11750 ft-lbs (15931 N-m)
Rated Speed in High Gear	96 RPM	101 RPM	76 RPM
Weight - lbs (kg)	672 (305)	716 (325)	716 (325)
Size Range	1.05" to 4-3/4" (26.7 to 120.6 mm)		
Standard Jaw and Bushing Assembly Sets (other sizes available upon request)	<b>Part Number</b>		<b>Weight</b>
2-3/8" (60.3 mm) Tubing	45291A/45292A		19 (8.6)
2-7/8" (73.0 mm) Tubing	45291B/45292B		17 (7.7)
3-1/2" (88.9 mm) Tubing	45291C/45292C		14 (6.4)
4-1/2" (114.3 mm) Tubing	45291D/45292D		9 (4.1)
Manual Backup with 2-3/8" - 3.668" Lug Jaw	45700		61 (27.7)
3-1/2" - 4-1/2" Lug Jaw	45424		7 (3.2)
Air Backup with 1.90" - 4-1/2" Jaws (Single)	55510-102P		350 (158.8)
Air Backup with 1.90" - 4-1/2" Jaws (Dual)	45000ABD		475 (215.5)
2-7/8" - 5-9/16" Insert	55157		0.9 (0.4)

**Model 45000, 55000, 56000 Tubing Tong**