



Description: The Model E tubing spider is for single string applications and can be operated via a pneumatic or hydraulic cylinder. Slip bodies and inserts provide 360° support for the tubing. Low marking inserts are optional. A removable gate allows the operator to move the spider off the string to pass large objects.

Specifications:

| Model | E | Weight lbs (kg) |
|---|------------------------|--------------------|
| Capacity | 350000 lbs (158757 kg) | |
| Tubing Spider Assembly without Slips | | |
| Pneumatic | 66000-100 | 860 (390) |
| Hydraulic | 66000H-100 | |
| Slip Body Assembly, 3-1/2" Nominal | 66621-100 | 105 (47.6) |
| Slip Insert Set, 3-1/2" Nominal | | |
| 2-3/8" (60.3 mm) Tubing | 66651-1 | 19 (8.6) |
| 2-7/8" (73.0 mm) Tubing | 66651-2 | 18 (8.2) |
| 3-1/2" (88.9 mm) Tubing | 66651-3 | 12 (5.4) |
| Slip Body Assembly, 5-1/2" Nominal | 66623-100 | 93 (42.2) |
| Slip Insert Set, 5-1/2" Nominal | | |
| 4" (101.6 mm) Tubing | 66653-1 | 39 (17.7) |
| 4-1/2" (114.3 mm) Tubing | 66653-2 | 33 (15.0) |
| 5" (127.0 mm) Tubing | 66653-3 | 26 (11.8) |
| 5-1/2" (139.7 mm) Tubing | 66653-4 | 18 (8.2) |
| Slip Body Assembly, 7" Nominal | 66624-100 | 80 (36.3) |
| Slip Insert Set, 7" Nominal | | |
| 5-1/2" (139.7 mm) Tubing | 66654-1 | 51 (23.1) |
| 6-5/8" (168.3 mm) Tubing | 66654-2 | 32 (14.5) |
| 7" (177.8 mm) Tubing | 66654-3 | 23 (10.4) |
| Slip Body, Integral Teeth, 7-5/8" (193.7 mm) Tubing | 66625-100 | 85 (38.6) |

Note: Specify Standard Tooth, Straight Tooth or Non-Marking when requesting insert sets.

Model E Tubing Spider