



Description: The RS and RS-HT (High Torque) powered tubing tongs are an open face design. Tongs come complete with spring hanger and are less jaws/bushings and backup. The hydraulic power requirements are 2000 PSI at 35 GPM, and the tong has a 39" torque arm.

Specifications:

Model	RS	RS-HT
Part Number	34891	34891-HT
Rated Torque in Low Gear	4650 ft-lbs (6305 N-m)	6650 ft-lbs (9016 N-m)
Rated Speed in High Gear	100 RPM	80 RPM
Weight - lbs (kg)	625 (284)	
Size Range	1.05" to 4-1/2" (26.7 to 114.3 mm)	
Standard Jaw and Bushing Assembly Sizes (other sizes available upon request)	Part Number	Weight
2-3/8" (60.3 mm) Tubing	Jaw / Bushing	lbs (kg)
2-7/8" (73.0 mm) Tubing	27477-1 / 27645-1	19 (8.6)
3-1/2" (88.9 mm) Tubing	27481-1 / 27660-1	17 (7.7)
4-1/2" (114.3 mm) Tubing	17912-1 / 17913-1	14 (6.4)
	24553-1 / 24552-1	9 (4.1)
Manual Backup with 2-3/8" - 3.668" Lug Jaw	30430-110	61 (27.7)
3-1/2" - 4-1/2" Lug Jaw	30424-6	7 (3.2)

Model RS Tubing Tong