



Description: The Model TS-100 tubing spider is for single string applications and is operated manually. It is offered in a 3-1/2" bowl and 5-1/2" bowl. The hinged body allows the operator to move the spider off the string to pass large objects.

Specifications:

Model	TS-100	Weight lbs (kg)
Capacity	200000 lbs (54431 kg)	
Tubing Spider Assembly without Slips		
3-1/2" Bowl	7502-100	195 (88)
5-1/2" Bowl	7502-103	245 (111)
Slip Body Assembly, 3-1/2" Nominal	7502-104	52 (23.6)
Slip Insert, 3-1/2" Nominal	(9 Each Required)	
1.050" (26.7 mm) Tubing	7502-A-5077	2.7 (1.22)
1.315" (33.4 mm) Tubing	7502-A-5076	2.3 (1.04)
1.660" (42.1 mm) Tubing	7502-A-5075	1.8 (0.82)
1.900" (48.2 mm) Tubing	7502-A-5074	1.7 (0.77)
2.060" (52.3 mm) Tubing	7502-A-5072	1.6 (0.73)
2-3/8" (60.3 mm) Tubing	7502-A-5071	1.4 (0.64)
2-7/8" (73.0 mm) Tubing	7502-A-5070	1.1 (0.50)
3-1/2" (88.9 mm) Tubing	7502-A-5069	0.7 (0.32)
Slip Body Assembly, 5-1/2" Nominal	7502-70	68 (30.8)
Slip Insert, 5-1/2" Nominal	(12 Each Required)	
3-1/2" (88.9 mm) Tubing	7502-F-26	2.6 (1.18)
4" (101.6 mm) Tubing	7502-G-26	2.0 (0.90)
4-1/2" (114.3 mm) Tubing	7502-C-26	1.8 (0.82)
5" (127.0 mm) Tubing	7502-D-26	1.4 (0.64)
5-1/2" (139.7 mm) Tubing	7502-A-26	1.0 (0.45)

Model TS-100 Tubing Spider