



Description: Slips are used to hold tubulars when making or breaking connections. They have a 4" taper and ship less inserts and with steel handles. Specify safety / flex handles if required.

Part Number	Cross Reference	Slip Size in	Insert Size in	Weight lbs
B Long Slip less Inserts (24 Inserts Required)				
738-244-0100	19-450	4-1/2	N/A	114
B Short Slip less Inserts (18 Inserts Required)				
738-144-0100	N/A	4-1/2	N/A	99
Inserts				
757-044-0144	19-250	4-1/2	4-1/2	0.9
757-044-0140	19-251	4-1/2	4	1.2
757-044-0134	19-252	4-1/2	3-1/2	1.8
757-044-0127	19-253	4-1/2	2-7/8	2.0
757-044-0123	19-254	4-1/2	2-3/8	2.2
19-255	N/A	4-1/2	2-1/16	2.5
Replacement Parts		Description		
737-000-0100	19-105	Left Handle		5.4
737-000-0200	19-104	Rear Handle		5.5
737-000-0300	19-102	Right Handle		5.4
737-000-0400	19-103	Handle Pin with Cotter		0.3
737-000-0500	19-101	Hinge Pin with Cotter		1.2
737-000-0600	19-106	Insert Retainer Pin with Cotter		0.3

Type B Rotary Slip