



**Description:** Safety clamps consist of tapered segments that wedge onto a tubular when the clamp is tightened. They help prevent slick or small upset tubulars from dropping downhole.

Part Number	Cross Reference	OD Range in (mm)	Links Req'd	Weight lbs (kg)
<b>Single Screw (CR)</b>				
7624-5055 (less box)	12-127	3-3/4 - 4-5/8 (95.3 - 117.5)	7	50 (22.7)
7624-5007 (with box)	12-127-B			100 (45.4)
7624-5056 (less box)	12-128	4-1/2 - 5-5/8 (114 - 142.9)	8	56 (25.4)
7624-5008 (with box)	12-128-B			106 (48.1)
7624-5057 (less box)	12-129	5-1/2 - 6-5/8 (139.7 - 168.3)	9	61 (27.7)
7624-5009 (with box)	12-129-B			111 (50.3)
7624-5058 (less box)	12-130	6-1/2 - 7-5/8 (165.1 - 193.7)	10	66 (29.9)
7624-5010 (with box)	12-130-B			116 (52.6)
7624-5059 (less box)	12-131	7-1/2 - 8-5/8 (190.5 - 219.1)	11	72 (32.7)
7624-5011 (with box)	12-131-B			122 (55.3)
7624-5060 (less box)	12-132	8-1/2 - 9-5/8 (215.9 - 244.5)	12	78 (35.4)
7624-5012 (with box)	12-132-B			128 (58.1)
7624-5061 (less box)	12-133	9-1/2 - 10-5/8 (241.3 - 269.9)	13	84 (38.1)
7624-5013 (with box)	12-133-B			134 (60.8)
<b>Single Screw (CL)</b>				
7624-5062 (less box)	12-134	10-1/2 - 11-5/8 (266.7-295.3)	14	90 (40.8)
7624-5014 (with box)	12-134-B			150 (68.0)
7624-5063 (less box)	12-135	11-1/2 - 12-5/8 (292.1-320.7)	15	96 (43.5)
7624-5015 (with box)	12-135-B			156 (70.8)
7624-5064 (less box)	12-136	12-1/2 - 13-5/8 (317.5-346.1)	16	102 (46.3)
7624-5016 (with box)	12-136-B			152 (68.9)
7624-5065 (less box)	12-137	13-1/2 - 14-5/8 (342.9-371.5)	17	108 (49.0)
7624-5017 (with box)	12-137-B			158 (71.7)
7624-5066 (less box)	12-138	14-1/2 - 15-5/8 (368.3-396.9)	18	114 (51.7)
7624-5018 (with box)	12-138-B			164 (74.4)

## Type C Safety Clamp



Part Number	Cross Reference	OD Range in (mm)	Links Req'd	Weight lbs (kg)
<b>Double Screw (CXL)</b>				
7624-5084 (less box)	12-145	15-1/2 - 17 (393.7 - 431.8)	18	120 (54.4)
7624-5029 (with box)	12-145-B			170 (77.1)
7624-5085 (less box)	12-146	16-1/2 - 18 (419.1 - 457.2)	19	126 (57.2)
7624-5030 (with box)	12-146-B			176 (79.8)
7624-5086 (less box)	12-147	17-1/2 - 19 (444.5 - 482.6)	20	132 (59.9)
7624-5031 (with box)	12-147-B			182 (82.6)
7624-5087 (less box)	12-148	18-1/2 - 20 (469.9 - 508)	21	138 (62.6)
7624-5032 (with box)	12-148-B			188 (85.3)
<b>Replacement Parts</b>		<b>Description</b>		
7624-A-7	12-101	Link Assembly Complete		5.0 (2.27)
7624-A-1	12-102	Link Intermediate		3.8 (1.72)
7624-A-4	12-103	Insert with Cotter		1.1 (0.5)
900620-65	12-104	Cotter for Insert		0.1 (0.05)
7624-E-5	12-105	Spring for Insert		0.1 (0.05)
7624-C-5	11-106	Link Pin with Cotter		0.8 (0.36)
900620-36	11-107	Cotter for Link Pin		0.1 (0.05)
7624-A-3	12-108	End Link (Screw)		4.5 (2.0)
7624-A-24	12-109	End Link (Pivot Block)		3.5 (1.6)
7624-F-5	11-110	End Link Pin with Chain		1.3 (0.6)
7624-A-5	11-111	Screw		4.0 (1.8)
7624-B-5	11-112	Nut		1.5 (0.7)
7624-A-5000	11-113	Pivot Block		1.5 (0.7)
7624-D-5	11-114	Pivot Block Pin		0.3 (0.14)
7624-A-25	11-115	Nut Wrench		4.0 (1.8)
7624-A-6	12-116	Handle		3.0 (1.4)
7624-G-5	11-117	Handle Link Pin with Cotter		0.8 (0.36)
7624-A-5135	12-118	Handle Kit		4.0 (1.8)
900533-12	11-119	Pivot Block Pin Wrench		0.1 (0.05)
7624-A-9	11-120	Safety Clamp Box		45 (20.4)

## Type C Safety Clamp