



Description: Slips are used to hold casing when making or breaking connections. The slips have a 4" taper and ship complete with buttons and steel handles. Specify safety / flex handles if required.

Part Number	Cross Reference	OD Size in	Seg. / Hinge Pin	Weight lbs	Spare Button Set	Weight lbs
98700	N/A	5-1/2"	11 / 10	174	2619-132	33
5315	98701 / 14-111	6-5/8"	12 / 11	196	2628-144	45
5301	98702 / 14-112	7"	12 / 11	184	2619-144	36
5303	98703 / 14-113	7-5/8"	12 / 11	166	2630-144	18
5305	98704 / 14-114	8-5/8"	13 / 12	181	2630-156	19.5
5307	98705 / 14-115	9-5/8"	14 / 13	192	2630-168	21
5309	98706 / 14-116	10-3/4"	15 / 14	209	2630-180	22.5
5311	98707 / 14-117	11-3/4"	17 / 16	260	2627-204	51
5313	98708 / 14-118	13-3/8"	18 / 17	278	2630-216	27
5325	98709 / 14-119	16"	21 / 20	308	2631-252	31.5
5333	98720 / 14-120	18-5/8"	25 / 24	367	2626-300	56
5329	98721 / 14-121	20"	26 / 25	383	2631-312	39
5331	98722 / 14-122	24"	30 / 29	443	2631-360	45
5346	98723 / 14-123	26"	33 / 32	486	2631-396	49.5
5342	98724 / 14-124	30"	37 / 36	546	2631-444	55.5
Replacement Parts		Description				
2525	98715 / 14-106	Hinge Pin with Cotter				0.7
3769	98717 / 14-105	Handle Pin with Washer and Cotter				0.5
3765	98714 / 14-104	Handle for Right / Left Hand Segment (Front)				3.5
3766	14-103	Handle for Intermediate Segment (Rear)				4
3748	N/A	Retaining Screw with Lock Washer				0.3

Type CMSXL Casing Slip