



Description: Slips are used to hold drill collars when making or breaking connections. They have a 4" taper and ship complete with buttons and steel handles. Specify safety / flex handles if required.

Part Number	Bowl	Cross Reference	OD Size in	Seg. / Hinge Pin	Weight lbs	Spare Button Set	Weight lbs
DCS-S							
2572	API / #3	16-120	3 - 4	7 / 6	112	2628-49	13
2573	API / #3	16-121	4 - 4-7/8	7 / 6	103	2620-49	8
DCS-R							
2552	API / #3	16-122	4-1/2 - 6	9 / 8	120	2628-63	16
2550	API / #3	16-123	5-1/2 - 7	9 / 8	112	2620-63	11
DCS-L							
2501	API / #3	16-125	5-1/2 - 7	11 / 10	172	2513-88	19
2503	API / #3	16-126	6-3/4 - 8-1/4	11 / 10	154	2630-88	15
2507	#3	16-127	8 - 9-1/2	12 / 11	173	2630-96	16
2530	#2	16-128	8-1/2 - 10	13 / 12	185	2627-104	26
2508	#2	16-129	9-1/4 - 11-1/4	14 / 13	198	2630-112	19
2534	#1	16-130	11 - 12-3/4	17 / 16	213	2625-136	20
2536	#1	16-131	12 - 14	17 / 16	207	2630-136	22
Replacement Parts				Description			
2525		98715 / 14-106	Hinge Pin with Cotter (DCS-S / DCS-R)			0.7	
2520		16-112	Hinge Pin with Cotter (DCS-L)			0.7	
3769		98717 / 14-105	Handle Pin with Washer and Cotter			0.5	
3765		98714 / 14-104	Handle for Right / Left Hand Segment (Front)			3.5	
3766		14-103	Handle for Intermediate Segment (Rear)			4	
3748		N/A	Retaining Screw with Lock Washer			0.3	

Type DCS-S / DCS-R / DCS-L Drill Collar Slip