



Description: Safety clamps consist of tapered segments that wedge onto a tubular when the clamp is tightened. They help prevent slick or small upset tubulars from dropping downhole.

Part Number	Cross Reference	OD Range in (mm)	Links Req'd	Weight lbs (kg)
7624-5103 (less box)	11-125	1-1/8 - 2 (28.6 - 50.8)	4	36 (16.3)
7624-5044 (with box)	11-125-B			84 (38.1)
7624-5104 (less box)	11-126	2-1/8 - 3-1/4 (54.0 - 82.6)	5	40 (18.1)
7624-5045 (with box)	11-126-B			88 (39.9)
7624-5105 (less box)	11-127	3-1/4 - 4-1/2 (82.6 - 114)	6	44 (20.0)
7624-5046 (with box)	11-127-B			92 (41.7)
Replacement Parts		Description		
7624-B-7	11-101	Link Assembly Complete		4.3 (2.0)
7624-A-18	11-102	Link Intermediate		3.3 (1.5)
7624-A-21	11-103	Insert with Cotter		0.3 (0.14)
900620-52	11-104	Cotter for Insert		0.1 (0.05)
7624-B-21	11-105	Spring for Insert		0.1 (0.05)
7624-C-5	11-106	Link Pin with Cotter		0.8 (0.36)
900620-36	11-107	Cotter for Link Pin		0.1 (0.05)
7624-A-20	11-108	End Link (Screw)		4.5 (2.0)
7624-A-19	11-109	End Link (Pivot Block)		3.5 (1.6)
7624-F-5	11-110	End Link Pin with Chain		1.3 (0.6)
7624-A-5	11-111	Screw		4.0 (1.8)
7624-B-5	11-112	Nut		1.5 (0.7)
7624-A-5000	11-113	Pivot Block		1.5 (0.7)
7624-D-5	11-114	Pivot Block Pin		0.3 (0.14)
7624-A-25	11-115	Nut Wrench		4.0 (1.8)
7624-A-22	11-116	Handle		3.0 (1.4)
7624-G-5	11-117	Handle Link Pin with Cotter		0.8 (0.36)
7624-A-5138	11-118	Handle Kit		4.0 (1.8)
900533-12	11-119	Pivot Block Pin Wrench		0.1 (0.05)
7624-A-9	11-120	Safety Clamp Box		45 (20.4)

Type T Safety Clamp